

APPLICATIONS

Cascade offers a number of fork mounted jib cranes that quickly convert a lift truck into a mobile crane to easily move non-palletised product. A variety of Jib Crane models for practically any application to increase lift truck versatility. Models include Multi-Angled, Flat, Slip-On, or Carriage- Mounted, allowing for effective slinging of loads beneath a hook. Unit secured to the forklift by safety locking pins or chain. Supplied with rating plate and rated safety swivel hook. The standard finish on this attachment is zinc.

SPECIFICATIONS

SWL	2500kg
H C of G	728mm
V C of G	225mm
Weight	226kg
Fork Pockets	160x60mm
Pocket Centres	346mm
Jib Height	605mm
Overall Length:	2222mm closed
Drawing Ref	SK-27314



Note: All lift truck attachments affect the safe working load of a lift truck. End users should consult their lift truck supplier to ensure the lift truck is rated for use with these attachments. In the case of a slung load when lifting a jib attachment, the net lifting capacity should be 0.8 times the rating of the lift truck to allow for the swinging load. Please consult your local lift truck

SAFE WORKING LOAD (SWL) PER POSITION								
POSITION	1	2	3	4	5	6	7	8
SWL (kg)	2500	2300	1900	1650	1150	660	400	250
EXTENSION (mm)	1005	1465	1925	2090	2460	2830	3200	3580

