

**APPLICATIONS**

Cascade offers a number of fork mounted jib cranes that quickly convert a lift truck into a mobile crane to easily move non-palletised product. A variety of Jib Crane models for practically any application to increase lift truck versatility. Models include Multi-Angled, Flat, Slip-On, or Carriage- Mounted, allowing for effective slinging of loads beneath a hook. Unit secured to the forklift by safety locking pins or chain. Supplied with rating plate and rated safety swivel hook. The standard finish on this attachment is zinc.

**SPECIFICATIONS**

SWL	4750kg
H C of G	985mm
V C of G	275mm
Weight	315kg
Fork Pockets	185x67mm
Pocket Centres	370mm
Jib Height:	655mm
Overall Length	2160mm closed
Drawing Ref	SK-27936



*Note: All lift truck attachments affect the safe working load of a lift truck. End users should consult their lift truck supplier to ensure the lift truck is rated for use with these attachments. In the case of a slung load when lifting a jib attachment, the net lifting capacity should be 0.8 times the rating of the lift truck to allow for the swinging load. Please consult your local lift truck dealer.*

SAFE WORKING LOAD (SWL) PER POSITION								
POSITION	1	2	3	4	5	6	7	8
SWL (kg)	4750	4150	3700	3300	2500	1300	760	480
EXTENSION (mm)	1060	1505	1950	2105	2475	3845	3220	3590

