

APPLICATIONS

Cascade offers a number of fork mounted jib cranes that quickly convert a lift truck into a mobile crane to easily move non-palletised product. A variety of Jib Crane models for practically any application to increase lift truck versatility. Models include Multi-Angled, Flat, Slip-On, or Carriage- Mounted, allowing for effective slinging of loads beneath a hook. Unit secured to the forklift by safety locking pins or chain. Supplied with rating plate and rated safety swivel hook. The standard finish on this attachment is zinc.

SPECIFICATIONS

SWL	2500kg
H C of G	501mm
V C of G	209mm
Weight	185kg
Fork Pockets	185x65mm
Pocket Centres	337mm
Jib Height	556mm
Overall Length	1350mm closed
Drawing Ref	SK-27315



SAFE WORKING LOAD (SWL) PER POS					
POSITION	1	2	3	4	5
SWL (kg)	2500	1800	1200	900	750
EXTENSION (mm)	830	1130	1290	1660	2030

Note: All lift truck attachments affect the safe working load of a lift truck. End users should consult their lift truck supplier to ensure the lift truck is rated for use with these attachments. In the case of a slung load when lifting a jib attachment, the net lifting capacity should be 0.8 times the rating of the lift truck to allow for the swinging load. Please consult your local lift truck

